

## TIPS : SURFACE PREPARATION FOR PAINTS

TYPE OF SURFACES	PREPARATION OF SURFACES	FINISHES
<b>On untreated surfaces:</b> Gypsum sheet	<ul> <li>Casein primer</li> <li>Caution! It is strongly recommended to apply a 2nd coat only to areas where joint cement has been used.</li> <li>Respect the drying time between each application.</li> </ul>	<ul> <li>Lime paint</li> <li>Clay paint</li> </ul>
On untreated surfaces: <ul> <li>Gypsum plaster</li> <li>Clay plaster</li> <li>Lime plaster</li> <li>Cement plaster</li> <li>Cement/lime plaster</li> </ul>	Casein primer	<ul> <li>Lime paint</li> <li>Clay paint</li> <li>GekkkoSOL paint</li> </ul>
On untreated surfaces: <ul> <li>Concrete*</li> <li>Brickwork</li> </ul> *Caution! Remove any residual formwork oil from the concrete.	Casein primer	<ul> <li>Lime paint</li> <li>Clay paint</li> <li>GekkkoSOL paint</li> </ul>
On untreated surfaces: <ul> <li>Cement sheet</li> <li>Cement block</li> </ul>	Casein primer	<ul> <li>Lime paint</li> <li>Clay paint</li> <li>GekkkoSOL paint</li> </ul>
<ul> <li>Old paint</li> <li>Others (following consultation)</li> </ul>	GekkkoSOL paint	<ul> <li>Lime paint</li> <li>Clay paint</li> <li>GekkkoSOL paint</li> </ul>

Caution! It is always advisable to carry out a test beforehand, especially if you are unfamiliar with the nature of the surface (composition).

NOTE: Quality acrylic-based synthetic primers may be compatible. However, it is imperative to carry out a test beforehand.

Always refer to the product data sheet for complete information. Make sure you have the latest version available on our website at <u>www.tockay.com</u>

