



## TIPS : HOW TO WELL PRESERVE THE FUNCTIONALITY OF TADELAKT IN WET ENVIRONMENTS



### SAOPING / MAINTENANCE / CLEANING

**Beauty and functionality of Tadelakt surfaces are easy to maintain.** Simply apply a soap solution every 1-2 months.

- Apply diluted polishing soap (1 part soap + 6 parts water) with a soft brush. After a short setting time (drying), polish the surface with a soft cloth rolled into a ball. It is also possible to use Marseille soap (item # 223) in the same way (2-3 teaspoons of soap + 2 liters of water).
- It is strongly recommended to **dry the shower walls with a soft cloth after** each use to avoid lime deposit due to water drops. Discoloration and mildew could appear if the Tadelakt remains wet for too long in matte areas.

### IMPORTANT NOTES:

It is imperative that the Tadelakt dries completely at least once a day. If the Tadelakt remains wet for too long, discolorations, fungus and dull stains may appear.

Avoid commercial household cleaning products (they contain anti-limescale), as well as scouring agents, scouring sponges, acidic cleaners or similar. These products will attack the Tadelakt !

Acidic juices such as orange or lemon juice, as well as wine and vinegar, can also damage the surface. Tadelakt surfaces are sensitive to acids. Substances containing fats and dyes (food, personal car products, etc.) can cause irreversible stains.

*This technical data sheet reflects our current state of knowledge. It does not guarantee the application of the product: this depends on the working methods, the nature of the support, the ambient temperature!*

*We advise you to check the suitability of the product for the properties of the substrate, and to carry out a sample test on a small surface beforehand. It is your responsibility to check that this sheet has not been modified or replaced by a more recent edition. Consult our website: [www.tockay.com](http://www.tockay.com)*

