



CASEIN PRIMER

Technical data sheet 145

■ GENERAL

Multi-purpose, colourless transparent primer for subsequent coats and thin-layer plastering with Tockay clay paint, lime paints and plasters. Tockay casein primer does not reduce the diffusion capacity of plasters (sD value < 0.01 m), which makes it an ideal primer, especially for clay and lime plasters.

■ USES

Suitable for use on all untreated substrates such as clay, lime, lime-cement, gypsum plasters, gypsum plasterboard and gypsum fibre boards, stone, concrete.

Recommended for priming absorbent old paints before renovation: e. g. Tockay casein-, clay-, lime- and emulsion paints.

Not suitable for all smooth, non-absorbent surfaces and permanently moist substrates.

For transparent solidification of plasters, especially clay plasters indoors; here it is necessary to create test areas (see chapter "Tips").

The use of casein primer within the different Tockay paint and plastering systems is described in the corresponding product information.

■ PROPERTIES

- Powder for mixing with water
- Reduces the absorbency of highly absorbent substrates and compensates different absorbencies of the substrates.
- Solidifies slightly sandy substrates.
- very good penetrating power
- colourless, transparent
- easy to process
- very economical
- highly diffusible.
- free of preservatives
- paint residues are compostable

■ COMPOSITION (FULL DECLARATION)

Casein, sodium carbonate.

■ SUITABLE TOOLS

Facade and ceiling brushes.

You will find quality facade and ceiling brushes in our assortment:

- Facade Brush (Article no. P 6080)
- Lime Brush (Article no. P 6082)
- Ceiling Brush (Article no. P 6054.1)

Do not spray or apply with a roller.

■ PREPARING THE SUBSTRATE

The substrate must be absorbent, clean, dry, solid, free of grease and free of penetrating and colouring substances.

- Thoroughly remove old distemper coats and other old chalking or unstable old paint coats. Thoroughly wash off any residual wallpaper glue from the substrate.
- Thoroughly remove dust from surfaces and thoroughly sweep sandy surfaces.
- Check old coatings for good adhesion and remove them if necessary.
- Remove accumulations of binders and sintered skin on plaster surfaces. Etch fresh lime-based plasters.
- Remove any residual mould oil on concrete.
- Remove loose parts of plaster, wall and repair with similar material.

Clean mould-affected mineral substrates with soda lye.

■ MIXING THE CASEIN PRIMER

For mixing the casein primer, it is best to use a 10-litre bucket and an agitator (drilling machine + whisk).

Add the casein primer (250 g) to 3 litres of clean cold water while stirring constantly. Make sure that all the lumps are mixed. After an expanding time of approx. 30 minutes, stir again thoroughly and dilute with 5 litres of water.

■ APPLICATION

Apply casein primer evenly and saturated.

Only apply as much liquid as is absorbed by the substrate. Remove excess material (wet glossy spots) with a cloth before drying.





CASEIN PRIMER

Technical data sheet 145

Application temperature min. 8°C.

The **Primer must be applied on the same day as mixing**. Do not use Primer that smells bad or rotten under any circumstances: Danger of prolonged odour problems even after drying!

■ DRYING TIMES

Dried after approx. 8 hours at 20°C and safe to coat with paints or plasters based on lime or clay.

■ CONSUMPTION / RANGE

Depending on the absorbency of the substrate, 250 g powder can be used for approx. 440 to 660 pi².

■ STORAGE

The powder can be stored in a cool, dry and frost-free place for at least 2 years.

■ PACKAGE SIZES

Art. No. 145 250 g (for 8L of primer)

■ CLEANING THE TOOLS

Immediately after use with water. If necessary, use Marseille soap.

■ DISPOSING LEFTOVER PRODUCT

Do not discharge product residues into the wastewater. Product residues can be composted or can be disposed of dried in the household waste.

■ TIPS

Transparent solidification of plasters:

For the transparent solidification of clay and other plasters without subsequent application of paint, we recommend Tockay Wall Glaze Binder (Art. 760). You will find detailed instructions on how to proceed in the corresponding product information.

■ EC VOC VALUE ACC. TO 2004/42/EC

VOC limit / Max. VOC content (cat. A/h): 30 g/l (2010), Product contains max. 1 g/l VOC.

■ HAZARD CLASSIFICATION

None, non-hazardous product.

■ WARNING

Pay attention to possible natural substance allergies. Due to the natural raw materials used, a typical product odour occurs which disappears in dry surroundings over time!

Keep out of reach of children.

The information above was determined based on our most recent experiences. Due to processing methods and environmental influences, as well as the varying nature of the substrates, liability for the general validity of the individual recommendations is excluded. Users must test the product prior to application to ensure it is fit for the designated purpose (sample coating).

This document is no longer valid if a new version is published, or the product is modified.

The latest product information is available on the Internet: www.tockay.com or www.kreidezeit.de

(Edition 09/2020)

