



# GEKKKOSOL THINNER

Technical Data Sheet 137

## ■ INGREDIENTS (FULL DECLARATION)

Waterglasses, water.

## ■ PACKAGE SIZES

Product ready to use in PE-bottles.

Art. 137..... 1 Litre

## ■ CLEANING TOOLS

Clean with water immediately after use.

## ■ STORAGE

GekkoSOL Thinner can be kept at least twelve months if stored airtight and above zero degrees centigrade.

## ■ DISPOSAL OF RESIDUES

Do not dispose of residues in the sink. Dried residues can be disposed of with normal household litter.

## ■ HAZARD CLASSIFICATION

Not applicable, non-hazardous product.

## ■ LABELING IN COMPLIANCE WITH DECOPAINT DIRECTIVE (2004/42/EC) ON SOLVENT CONTENT

Maximum VOC content (cat. A/a): 30 g/l (2010), product contains a maximum of 1 g/l VOC.

## ■ SAFETY ADVICE / INDICATIONS

Protect eyes and skin during application (protective goggles and gloves). In case of contact with eyes or skin, rinse thoroughly with clear water and consult a doctor (ophthalmologist).

Protect surfaces not to be treated from splashes of product or remove splashes immediately with water (risk of irreversible stains!).

Tockay GekkoSOL mineral paint (smooth or textured) must not be diluted with potassium silicate or water, but only with GekkoSOL thinner.

**This product may cause allergies to natural substances. Keep out of reach of children.**

*The above information has been compiled in accordance with the best of our experience and knowledge. Owing to the application methods and environmental influences, as well as the various surface properties, no liabilities or legalities pertaining to the individual recommendations can be entertained. Prior to application, the suitability of the product is to be tested (trial coat). The validity of the text ceases with revisions or product modifications.*

You will find the latest product information at: [www.tockay.com](http://www.tockay.com) or [www.kreidezeit.de](http://www.kreidezeit.de)

(Edition 08/2021)

