



# PUNIC WAX

Technical Data Sheet 196

## ■ GENERAL

Punic Wax is a soap based on beeswax with a creamy consistency. The beeswax is molten, cleaned and then bleached with active charcoal and Fuller's earth using a special method.

In a process developed by KREIDEZEIT the bleached wax is saponified with potash so that it is partly water soluble and easy to apply.

## ■ UTILISATION

Punic Wax is a shiny wax coating for:

- Stucco Fine-, Tadelakt-, Marmorino works, and on Lime Wall Finish -smooth-
- marble imitations (e.g. on Casein Marble Paint)
- Encaustic
- Casein Paint Coatings

## ■ PROPERTIES

- Creamy, paste-like
- Low odour
- Without organic solvents (the solvent is water)
- Satin-finished to high-gloss after polishing
- Dirt-repelling
- Antistatic
- Diffusible

## ■ COMPOSITION (FULL DECLARATION)

Water, beeswax, potash, silicic acid.

## ■ APPLICATION

**On Marmorino, Stucco Fein, Lime wall Finish -smooth-**  
Apply Punic wax undiluted with the Venetian Trowel in one to several wafer-thin layers. Apply only to surfaces that have already been soaped. After drying, polish with a trowel.

## **On Tadelakt**

Apply Punic wax undiluted and wafer-thin with a cloth ball and polish immediately with a clean, dry and soft cloth ball. Apply only to surfaces that have already been soaped.

## Marble imitations

For example, on Casein Marble Paint (0.75 kg for 5 kg of powder) designed with marble imitations: apply the Punic Wax thinly with a trowel and, after drying, either polish with a trowel or by hand with soft cloths, horsehair brushes or a polishing machine for an even shine. Attention with machine polish: Too high pressure and too high rpm can lead to damage of the surface due to heat development!

The wax coating creates a deep and transparent character that is deceptively similar to real marble.

## ■ DRYING TIMES

Approx. 5 - 6 hours at 20 °C.

## ■ APPLICATION RATES

Approx. 30 g / m<sup>2</sup> (11 sq.ft.)

## ■ CONTAINER SIZES

Article no. 196.....400 g

## ■ CLEANING THE TOOLS

Immediately after use with warm water, if necessary, with a little soap.

## ■ STORAGE

Stored airtightly sealed and in a cool, dry, frost-free and place, shelf life at least 1 year.

## ■ DISPOSAL OF RESIDUES

Do not dispose of residues in the sink. Dried residues can be disposed of with normal household litter.

## ■ WARNING

Punic wax is alkaline. Avoid eye contact. In case of skin and eye contact, rinse with plenty of water, also under the eyelids. Pay attention to possible natural substance allergies. The natural raw materials used produce a typical product smell! Keep out of reach of children.

## ■ EU COV VALUE ACC. TO 2004/42/EC

VOC limit / Max. VOC content (cat. A/I): 200 g/l (2010), Product contains max. 1 g/l VOC.





# PUNIC WAX

Technical Data Sheet 196

---

## Keep out of reach of children.

*The above information has been compiled in accordance with the best of our experience and knowledge. Owing to the application methods and environmental influences, as well as the various surface properties, no liabilities or legalities pertaining to the individual recommendations can be entertained. Prior to application, the suitability of the product is to be tested (trial coat). The validity of the text ceases with revisions or product modifications.*

You will find the latest product information at:  
[www.tockay.com](http://www.tockay.com) or [www.kreidezeit.de](http://www.kreidezeit.de)

(Edition 09/2020)

